

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 07/16/2020 Version: 1.0

SECTION 1: Identifica	tion		
1.1. Identification			
Product form		: Mixture	
Product name		: 280 LOW VOC GLAZE PURE WHITE	
Product code		: 280T1000B	
1.2. Recommended us	se and restriction	ns on use	
Recommended use		: Industrial use	
Restrictions on use		: The product is intended for professional use	
1.3. Supplier			
Sumter Coatings, Inc. 2410 Hwy 15 South Sumter, SC 29150 - United T 803-481-3400 - F 803-48 info@sumtercoatings.com -	1-3776	tings.com	
1.4. Emergency teleph	none number		
Emergency number		: 800-255-3924 Chemtel	
SECTION 2: Hazard(s	) idontificatio	n	
2.1. Classification of t			
GHS US classification	ne substance of	IIIXUU6	
Flammable liquids	H224	Extremely flammable liquid and vapor	
Category 1	HZ24		
Skin corrosion/irritation	H315	Causes skin irritation	
Category 2 Germ cell mutagenicity Category 1B	H340	May cause genetic defects	
Carcinogenicity Category	H350	May cause cancer	
1B Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure	
Full text of H statements : se	e section 16		
2.2. GHS Label elemen GHS US labeling	nts, including pr	ecautionary statements	
Hazard pictograms (GHS U	IS)		
Tiazaru pictograms (CFIS C	3)		
Signal word (GHS US)		: Danger	
Hazard statements (GHS U	S)	: H224 - Extremely flammable liquid and vapor H315 - Causes skin irritation H340 - May cause genetic defects H350 - May cause cancer H373 - May cause damage to organs through prolonged or repeated exposure	
Precautionary statements (	GHS US)	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</li> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground/Bond container and receiving equipment.</li> </ul>	

- P240 Ground/Bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash hands, forearms and face thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Titanium Dioxide	(CAS-No.) 13463-67-7	30.78 – 34.2	Carc. 2, H351
XYLENE	(CAS-No.) 1330-20-7	8.236 – 10.793	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
ethylbenzene	(CAS-No.) 100-41-4	3.571 – 7.703	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
METHYL NORMAL AMYL KETONE	(CAS-No.) 110-43-0	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
AROMATIC 100	(CAS-No.) 64742-95-6	4.151 – 4.165	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms and effe	cts (acute and delayed)
Symptoms/effects after skin contact	: Irritation.
4.3. Immediate medical attention and s	pecial treatment, if necessary
Treat symptomatically.	
<b>SECTION 5: Fire-fighting measures</b>	
5.1. Suitable (and unsuitable) extinguis	hing media
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
5.2. Specific hazards arising from the c	hemical
Fire hazard	: Extremely flammable liquid and vapor.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3.	Special protective equipment and pr	eca	utions for fire-fighters
Protect	tion during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTI	ON 6: Accidental release meas	sur	es
6.1.	Personal precautions, protective equ	uipn	nent and emergency procedures
6.1.1.	For non-emergency personnel		
Emerg	ency procedures	:	No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.
6.1.2.	For emergency responders		
Protect	tive equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2.	Environmental precautions		
Avoid re	lease to the environment. Notify authoriti	es if	product enters sewers or public waters.
6.3.	Methods and material for containme	nt a	nd cleaning up
Method	ds for cleaning up	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other i	nformation	:	Dispose of materials or solid residues at an authorized site.
6.4.	Reference to other sections		
For furth	er information refer to section 13.		
SECTI	ON 7: Handling and storage		
7.1.	Precautions for safe handling		
Precau	tions for safe handling	:	Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
Hygien	e measures	:	Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2.	Conditions for safe storage, includir	ng a	ny incompatibilities
Techni	cal measures	:	Ground/bond container and receiving equipment.
Storag	e conditions	:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

AROMATIC 100 (64742-95-6)			
Not applicable			
XYLENE (1330-20-7)			
ACGIH	Local name	Xylene, mixed isomers (Dimethylbenzene)	
ACGIH	ACGIH TWA (ppm)	100 ppm	
ACGIH	ACGIH STEL (ppm)	150 ppm	
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
ACGIH	Regulatory reference	ACGIH 2019	
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>	
OSHA	OSHA PEL (TWA) (ppm)	100 ppm	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

XYLENE (1330-20-	,	
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
ethylbenzene (100	-41-4)	
ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BE
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
METHYL NORMAL	AMYL KETONE (110-43-0)	
ACGIH	Local name	Methyl n-amyl ketone
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & skin irr
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	465 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Titanium Dioxide (	13463-67-7)	
ACGIH	Local name	Titanium dioxide
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### 8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls Ensure good ventilation of the work station.Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

#### **Respiratory protection:**

Wear respiratory protection.

Personal protective equipment symbol(s):

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and ch	emical properties	
Physical state	: Liquid	
Appearance	: Liquid.	
Color	: white	
Odor	: characteristic	
Odor threshold	: No data available	
рН	: No data available	
Melting point	: Not applicable	
Freezing point	: No data available	
Boiling point	: No data available	
Flash point	: 39 °F Based on data available for ingredients	
Relative evaporation rate (butyl acetate=1)	: No data available	
Flammability (solid, gas)	: Not applicable.	
Vapor pressure	: No data available	
Relative vapor density at 20 °C	: No data available	
Relative density	: No data available	
Solubility	: No data available	
Partition coefficient n-octanol/water (Log Pow)	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosion limits	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
9.2. Other information		

No additional information available

SECT	ON 10: Stability and reactivity
10.1.	Reactivity
Extrem	y flammable liquid and vapor.
10.2.	Chemical stability
Stable	nder normal conditions.
10.3.	Possibility of hazardous reactions
No dan	erous reactions known under normal conditions of use.
10.4.	Conditions to avoid
Avoid c	ntact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
10.5.	Incompatible materials
No add	onal information available
10.6.	Hazardous decomposition products
Under r	rmal conditions of storage and use, hazardous decomposition products should not be produced.
SECT	ON 11: Toxicological information
11.1.	Information on toxicological effects
Acute	oxicity (oral) : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
XYLENE (1330-20-7)	> 2609 ma/kg (Dat Oral)
LD50 oral rat	> 3608 mg/kg (Rat, Oral)
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
METHYL NORMAL AMYL KETONE (110-	
LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimenta value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
XYLENE (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposu	
Specific target organ toxicity – single exposu Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
ethylbenzene (100-41-4)	
Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
07/16/2020	EN (English LIS)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26	, 2012 /	Rules and Regulations
--	----------	-----------------------

Viscosity,	kinematic

Symptoms/effects after skin contact

: No data available

: Irritation.

Symptoms/encets after skin contact

### **SECTION 12: Ecological information**

No ecotoxicological studies have been conducted on this product by Sumter Coatings.

SECTION 13: Disposal consideration	ations
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.
SECTION 14: Transport information	tion

### Department of Transportation (DOT)

In accordance with DOT

Transport document description UN-No.(DOT) Proper Shipping Name (DOT) Class (DOT) Packing group (DOT) Hazard labels (DOT)

- : UN1263 Paint, 3, II
- : UN1263
- : Paint
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : II Medium Danger
- : 3 Flammable liquid



### SECTION 15: Regulatory information

### 15.1. US Federal regulations

AROMATIC 100 (64742-95-6)			
ted on the United States TSCA (Toxic Substances Control Act) inventory			
(YLENE (1330-20-7)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	100 lb		
ethylbenzene (100-41-4)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	1000 lb		
METHYL NORMAL AMYL KETONE (110-43-0)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Titanium Dioxide (13463-67-7)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			

### 15.2. International regulations

### CANADA

AROMATIC 100 (64742-95-6)		
Listed on the Canadian DSL (Domestic Substances List)		
XYLENE (1330-20-7)		

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	thylbenzene (100-41-4)	
	Listed on the Canadian DSL (Domestic Substances List)	
	METHYL NORMAL AMYL KETONE (110-43-0)	
Listed on the Canadian DSL (Domestic Substances List)		
	Titanium Dioxide (13463-67-7)	
	Listed on the Canadian DSL (Domestic Substances List)	

#### **EU-Regulations**

No additional information available

#### **National regulations**

Listed on IARC (International Agency for Research on Cancer) Titanium Dioxide (13463-67-7)	
Titanium Dioxide (13463-67-7)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Full text of H-phrases:

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

#### SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.