



**CROSSLINK III**  
**ADHESIVE**  
**480X1919**

**PRODUCT DESCRIPTION**

**PRODUCT:** Crosslink III Adhesive.

**TYPE:** Spray-on/wipe-on adhesion promoter primer.

**DESCRIPTION:** Topkote Crosslink III Adhesive is an adhesion promoter that can be used over all tub, tile and countertop surfaces including fiberglass & acrylics and eliminates the need for etching.

**USES:** Interior porcelain, ceramics, fiberglass, cultured marble, acrylic, laminates, metal and glass surfaces. Well suited for spray application on clean, properly prepared bathtubs, tile and countertop surfaces.

**MIXING:** No mixing is required before or during use. Dilution is not required.

**APPLICATION:** Using an HVLP sprayer apply 2 coats of Topkote Crosslink III, one horizontal and one vertical. You may also wipe it on, but spraying on eliminates the possibility of missing an area and maximizes coverage.

**SHELF LIFE:** Shelf life is one year unopened. This product is moisture sensitive, once the can has been opened, use within 30 days. Be sure to close lid tightly after use to prevent moisture from entering the container which can cause product to jell.

**TECHNICAL INFORMATION**

**SURFACE PREPARATION:** Surface must be clean and free of wax, polish, loose rust, oil, grease and moisture. Surface temp must be above 62°F. Old paint films which are soft, cracked or not firmly adhering to the surface may lift and wrinkle when Crosslink III Adhesive is applied over them. In such cases, the old finish should be removed. As a test, apply to a small inconspicuous area to determine compatibility.

**TYPICAL PROPERTIES:**

Appearance	Clear Liquid
Viscosity:	0.0 – 8.0
Weight/Gallon:	7.385 lb/gl
Solids by Weight:	12.927%
Flash Point:	40° F
Solvents:	Toluene, Isopropanol
VOC:	6.43 lb/gl

**CAUTIONARY INFORMATION:** Before using this product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

This product must be applied by trained personnel only. Not for consumer use.

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with [Sumter Coatings, Inc.](http://www.sumtercoatings.com) prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.'s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.