

## SECTION 1: Identification

### 1.1. Identification

Product form : Mixture  
 Product name : LOW VOC EPOXY SEMI GLOSS CATALYST  
 Product code : 214X4444A

### 1.2. Recommended use and restrictions on use

Recommended use : Industrial use  
 Restrictions on use : The product is intended for professional use

### 1.3. Supplier

Sumter Coatings, Inc.  
 2410 Hwy 15 South  
 Sumter, SC 29150 - United States  
 T 803-481-3400 - F 803-481-3776  
[info@sumtercoatings.com](mailto:info@sumtercoatings.com) - [www.sumtercoatings.com](http://www.sumtercoatings.com)

### 1.4. Emergency telephone number

Emergency number : 800-255-3924 Chemtel

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS US classification

Flammable liquids Category 1	H224	Extremely flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Carcinogenicity Category 1A	H350	May cause cancer

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H224 - Extremely flammable liquid and vapor  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H350 - May cause cancer

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 - Keep container tightly closed.  
 P240 - Ground/Bond container and receiving equipment.  
 P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 - Use only non-sparking tools.  
 P243 - Take precautionary measures against static discharge.  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Poly(Bisphenol A-co-epichlorohydrin), glycidyl end-capped	(CAS-No.) 25036-25-3	20 – 50	Skin Sens. 1, H317
bisphenol-A-(epichlorohydrin) epoxy resin	(CAS-No.) 25068-38-6	10 – 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Talc (Magnesium Silicate)	(CAS-No.) 14807-96-6	2.636 – 5.273	Carc. 2, H351
METHYL NORMAL AMYL KETONE - 6.74	(CAS-No.) 110-43-0	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
d'LIMONENE	(CAS-No.) 5989-27-5	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317
ethanol	(CAS-No.) 64-17-5	< 0.232	Flam. Liq. 2, H225 Carc. 1A, H350
ethylbenzene	(CAS-No.) 100-41-4	0.116 – 0.232	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
MICROCRYSTALLINE SILICA	(CAS-No.) 14808-60-7	0 – 0.2	Carc. 1A, H350 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable liquid and vapor.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### bisphenol-A(epichlorhydrin) epoxy resin (25068-38-6)

Not applicable

#### METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)

ACGIH

Local name

Methyl n-amyl ketone

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)

ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & skin irr
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	465 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### ethanol (64-17-5)

ACGIH	Local name	Ethanol
ACGIH	ACGIH STEL (ppm)	1000 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### ethylbenzene (100-41-4)

ACGIH	Local name	Ethylbenzene
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

### Poly(Bisphenol A-co-epichlorohydrin), glycidyl end-capped (25036-25-3)

Not applicable

### Talc (Magnesium Silicate) (14807-96-6)

ACGIH	Local name	Talc
ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination)
ACGIH	ACGIH TWA (ppm)	0.1 fibers/cm³ (Containing asbestos fibers. F - Respirable fibers)
ACGIH	Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis; pulm func. Notations: A4 Containing asbestos fibers = TLV® Basis: Pneumoconiosis; lung cancer; mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

### MICROCRYSTALLINE SILICA (14808-60-7)

ACGIH	Local name	Silica crystalline - quartz
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (Respirable fraction)

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

MICROCRYSTALLINE SILICA (14808-60-7)		
ACGIH	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2019
d'LIMONENE (5989-27-5)		
Not applicable		

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Mixture contains one or more component(s) which have the following color(s):  
Yellow Colourless to light yellow Colourless White White to dark grey White to light grey  
Colourless to white  
Odor : characteristic  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 64 °F Based on data available for ingredients  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20°C : No data available  
Relative density : No data available  
Density : 9.44 lb/gal  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content	: 1.28 lb/gal Based on data available for ingredients
-------------	---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### bisphenol-A-(epichlorhydrin) epoxy resin (25068-38-6)

LD50 oral rat	> 2000 mg/kg (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)

#### METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)

LD50 oral rat	1600 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 16.7 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1600 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

#### ethanol (64-17-5)

LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	125 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	10470 mg/kg body weight

#### ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>ethylbenzene (100-41-4)</b>	
ATE US (oral)	3500 mg/kg body weight
ATE US (dermal)	15432 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	17.8 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>Poly(Bisphenol A-co-epichlorohydrin), glycidyl end-capped (25036-25-3)</b>	
LD50 oral rat	11400 mg/kg (Rat, Oral)
ATE US (oral)	11400 mg/kg body weight

<b>d'LIMONENE (5989-27-5)</b>	
LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Weight of evidence, Dermal)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.

<b>ethanol (64-17-5)</b>	
IARC group	1 - Carcinogenic to humans

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>Talc (Magnesium Silicate) (14807-96-6)</b>	
IARC group	3 - Not classifiable, 2B - Possibly carcinogenic to humans

<b>MICROCRYSTALLINE SILICA (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans

<b>d'LIMONENE (5989-27-5)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

STOT-repeated exposure	: Not classified
------------------------	------------------

<b>ethylbenzene (100-41-4)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>MICROCRYSTALLINE SILICA (14808-60-7)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

No ecotoxicological studies have been conducted on this product by Sumter Coatings.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1263 Paint, 3, II
UN-No. (DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid



### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### bisphenol-A(epichlorhydrin) epoxy resin (25068-38-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

##### METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ

1000 lb

##### Poly(Bisphenol A-co-epichlorohydrin), glycidyl end-capped (25036-25-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

##### Talc (Magnesium Silicate) (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### MICROCRYSTALLINE SILICA (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### d'LIMONENE (5989-27-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

##### CANADA

##### bisphenol-A(epichlorhydrin) epoxy resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

##### METHYL NORMAL AMYL KETONE - 6.74 (110-43-0)

Listed on the Canadian DSL (Domestic Substances List)

##### ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

##### ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)



# 214X4444A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Poly(Bisphenol A-co-epichlorohydrin), glycidyl end-capped (25036-25-3)

Listed on the Canadian DSL (Domestic Substances List)

### Talc (Magnesium Silicate) (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

### MICROCRYSTALLINE SILICA (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

### d'LIMONENE (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)


#### ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

#### MICROCRYSTALLINE SILICA (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

 **WARNING:** This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*