

PRODUCT DESCRIPTION

2000 Epoxy Primer is a superior, high performance epoxy primer system designed for kitchen and bathroom refinishing.

2000 Epoxy Primer is an excellent undercoat on:

- Porcelain
- Ceramic Tile
- Bathroom Partitions
- Fiberglass
- Acrylic Inserts
- Formica Countertops

MIXING & APPLICATION

- **2000 Epoxy Primer** is a two-component system consisting of the base and catalyst (346X2200A).
- Both components' temperature must be above 55° F before intermixing.
- Mixing ratio is four parts base to one part 2000 Epoxy Catalyst (346X2200A) by volume.
- Thoroughly mix by mechanical agitation prior to use, if possible.
- This product has a 10 – 15 minute induction time after mixing and has a pot life of approximately two hours.

THINNING: Not recommended.

CLEAN UP: Acetone

SURFACE PREPARATION: Surface must be clean, dry, and free of moisture, oil, grease, loose paint, rust, silicone, polishes and waxes.

APPLICATION: Apply using an HVLP spray system equipped with a 1.0mm up to 1.5mm air cap set or conventional air system.

NOTE: For porcelain and ceramic, it is recommended to etch with an acid based cleaning solution prior to application of primer.

TECHNICAL INFORMATION

Type	Two-Component Epoxy Primer
Components - Two	Base (346 Line) Catalyst (346X2200A)
Volume Solids	35.19% ± 2%
Gloss	Flat
Coverage	One gallon of catalyzed material will cover approximately 564 sq ft/gal @ 1 mil dft.
Recommended DFT	1.5 – 3.0 mils dry film 188 - 376 sq ft/gal @ recommended dft
VOC	< 4.40 lbs/gal
Dry to Touch	15 min @ 77° F
Tack Free	30 – 45 min @ 77° F
Topcoat	1 hour @ 77° F
Pot Life	2 hours @ 70° F Do not use material that has exceeded its pot life.
Shelf Life	Two years (non-activated)
Flash Point	Combined base and catalyst - 64° F minimum

Rev 01/2026

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.