

PRODUCT DESCRIPTION



UR Urethane 4 Hour Dry Accelerator is a special additive designed to reduce the dry time without affecting the ultimate physical properties. Use primarily when offering same day use or two tone applications.

Features & Benefits

- Compatible with UR Glaze or 280 Low VOC topcoats
- Reduces cure time
- Minimal influence on pot life

INSTRUCTIONS

Substrate should be prepared and primed according to topcoat instructions prior to topcoat application. Add no more than 1/4 ounce accelerator to 15 ounces mixed material (glaze & activator) or 2 ounces accelerator to 1 gallon mixed material (glaze & activator). **DO NOT EXCEED RECOMMENDED AMOUNTS.**

PHYSICAL PROPERTIES

Composition	Paint Additive
Weight	8.12 lb/gl
VOC	9.65 lb/gl
Shelf Life	N/A
Flash Point	101°F
Safety Information	For additional Information, see SDS

Rev 01/2026

TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.