

## PRODUCT DESCRIPTION



Roll-A-Glaze is a brush/roll additive designed to be mixed in Topkote's 280 Low VOC or UR Glaze to provide maximum leveling and flow when brush or roller application is preferred. The special blend of ingredients allows more open time for workability and anti-foam agents help alleviate bubble formation.

### **Roll-A-Glaze features, advantages and benefits:**

- Turn your existing coating into a brush/roll system
- Minimize overspray
- Maximum leveling and flow

### **INSTRUCTIONS:**

Substrate should be prepared and primed according to topcoat instructions prior to topcoat application. Mix ratio is 4 parts glaze, 1 part activator and 2 parts brush/roll additive. Do not add reducer. Apply 1 wet coat at approximately 2-3 mils.

### **EQUIPMENT:**

It is important to apply the glaze with high quality applicators. For best results use a high quality 3" All Paints brush. You can also use a 6" foam roller.

## SAFETY

### **Respirator**

Use a properly fitted, air-purifying respirator complying with an approved standard.

### **Ventilation**

Use only with adequate ventilation.

## PHYSICAL PROPERTIES

Composition	Paint Additive
Weight	7.51 lb/gl
VOC	6.88 lb/gl
Shelf Life	N/A
Flash Point	109°F (40°C)
Safety Information	For additional Information, see SDS

Rev 01/2026

### **TERMS AND CONDITIONS OF SALE**

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.