



Fade-In Edge Blender 560X2801/430X2801

PRODUCT DESCRIPTION



Fade-In Edge Blender is a blending solvent that is used to dissolve and blend the dry spray edges on touch-ups and repairs.

Fade-In features, advantages and benefits:

- Easy to use
- Convenient
- Increased efficiency
- Available in aerosol for quick “spray gun” like blending
- Invisible blend

APPLICATION:

Hold the can 8-10” from the surface and apply a light mist of **Fade-In** in 1-2 rapid passes immediately after the application of the final topcoat. Be sure to move the can quickly. **DO NOT OVERAPPLY AS THIS COULD CAUSE RUNS.** Let flash a few minutes and if necessary apply again to eliminate the dry edges.

TECHNICAL INFORMATION

PHYSICAL PROPERTIES 560X2801

Volume Ratio	As is
Applicable Use	Uniform Finish
VOC Actual lbs/gal	7.547
VOC Regulatory lbs/gal	7.547
1.0 mil. Sq. Ft. Coverage / U.S Gal @ 100% Transfer Efficiency	53

PHYSICAL PROPERTIES 430X2801

Volume Ratio	As is
Applicable Use	Aerosol Uniform Finish
VOC Actual lbs/gal	6.499
VOC Regulatory lbs/gal	6.499
1.0 mil. Sq. Ft. Coverage / U.S Gal @ 100% Transfer Efficiency	24

See Safety Data Sheet and Labels for additional safety information and handling instructions

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with Sumter Coatings, Inc. prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.’s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.