



## UR Urethane 4 Hour Dry Accelerator 480X1994

### PRODUCT DESCRIPTION



**UR Urethane 4 Hour Dry Accelerator** is a special additive designed to reduce the dry time without affecting the ultimate physical properties. Use primarily when offering same day use or two tone applications.

#### Features & Benefits

- Compatible with UR Glaze or 280 Low VOC topcoats
- Reduces cure time
- Minimal influence on pot life

### INSTRUCTIONS

Substrate should be prepared and primed according to topcoat instructions prior to topcoat application. Add no more than ¼ ounce accelerator to 15 ounces mixed material (glaze & activator) or 2 ounces accelerator to 1 gallon mixed material (glaze & activator). **DO NOT EXCEED RECOMMENDED AMOUNTS.**

### PHYSICAL PROPERTIES

Composition	Paint Additive
Weight	8.12 lb/gl
VOC	9.65 lb/gl
Shelf Life	N/A
Flash Point	101°F
Safety Information	For additional Information, see SDS

**See Safety Data Sheet and Labels for additional safety information and handling instructions**

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with Sumter Coatings, Inc. prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.'s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.