



Fisheye Eliminator 480X4207

PRODUCT DESCRIPTION



Fisheye Eliminator is a special additive designed to help Topkote urethanes flow out on contaminated surfaces. Using **Fisheye Eliminator** will decrease the possibility of fish eyes by lowering the surface tension of the urethane to which it is added.

Features & Benefits

- Compatible with UR Glaze or 280 Low VOC topcoats
- Decrease fisheyes
- Reduce cratering

INSTRUCTIONS

Substrate should be prepared and primed according to topcoat instructions prior to topcoat application. Add no more than ¼ ounce **Fisheye Eliminator** to 15 ounces mixed material (glaze & activator) or 2 ounces **Fisheye Eliminator** to 1 gallon mixed material (glaze & activator). **DO NOT EXCEED RECOMMENDED AMOUNTS.**

PHYSICAL PROPERTIES

Composition	Paint Additive
Weight	7.32 lb/gl
VOC	6.58 lb/gl
Shelf Life	N/A
Flash Point	77°F
Safety Information	For additional Information, see SDS

See Safety Data Sheet and Labels for additional safety information and handling instructions

The technical data furnished are true and accurate to the best of our knowledge at the date of issuance. It is subject to change without prior notice. It is suggested the user verify with Sumter Coatings, Inc. prior to specifying or ordering. Test results are believed to be reliable; however, no guarantee of accuracy is given or implied. We guarantee all products to conform to Sumter Coatings, Inc.'s quality control standards. Liability, if any, is limited to replacement of product. No other warranty or guarantee of any kind, expressed or implied, is made by Sumter Coatings, Inc., including fitness for a particular purpose.